

**STANDARD FEATURES**

- ◆ 8½" high x 8" deep
- ◆ 1/5 hp direct driven motor(s)
- ◆ Aluminum air directional vanes
- ◆ White powder coated or stainless steel cabinet
- ◆ Wall mounting plate
- ◆ Threaded inserts for top mounting
- ◆ Aluminum cross-flow blower wheels
- ◆ UL listed (United States & Canada)
- ◆ Five year parts warranty
- ◆ Crafted with Pride in the USA

WHITE POWDER COATED	MODEL STAINLESS STEEL	Unit Width (in)	Max. Velocity (fpm)	Avg. Outlet Velocity (fpm)	Air Volume (scfm)	Motor(s) @ hp	Power Rating (kW)	Outlet Velocity Uniformity (%)	Net Wgt (lbs)	Ship Wgt (lbs)
KZN1030A	KZN1030A-SS	30.58	3300	1357	677	1 @ 1/5	.18	89	31	39
KZN1036A	KZN1036A-SS	36.06	3300	1786	1020	1 @ 1/5	.32	94	35	41
KZN1042A	KZN1042A-SS	42.06	3300	1773	1188	1 @ 1/5	.32	94	38	47
KZN1048A	KZN1048A-SS	48.06	3300	1768	1360	1 @ 1/5	.32	94	42	49
KZN1060A	KZN1060A-SS	59.56	3300	1689	1656	1 @ 1/5	.32	94	49	66
KZN1072A	KZN1072A-SS	72.81	3300	1725	2031	1 @ 1/5	.32	94	56	74

MOTOR VOLTAGES/AMP DRAWS					
Volts	120	208	240	120*	240*
Phase	1	1	1	1	1
Hertz	60	60	60	50	50
Amps per Motor	3.4	1.7	1.7	2.8	1.4

\* Operation at 50 Hz will generate approximately a 17% reduction in performance.

VELOCITY PROJECTION <i>Model KZN1036A</i>			
Distance from Nozzle (ft)	2	3	4
Core Velocity (fpm)	2260	1930	1728

Sound level measured 10' (3m) from the unit in free field:  
1 Motor **54 dBA**



ANSI/NSF 37  
Air Curtain Fans for  
Customer Entry  
12CS



for outdoor use  
stainless steel only



*Berner reserves the right to alter specifications without prior notice.*