



| Commercial Series | | |
|---|--------------------------------------|--------------|
|  | LoPro Drive Up Window | LoPro |
| Recommended Maximum Mounting Height (Feet) | | |
| Environmental Separation | 5' | 8' |
| Insect Control | 5' | 7' |
| Drive Up / Concession | • | • |
| Customer Entry | | • |
| Service Door | | |
| Shipping/Receiving | | |
| Freezer/Cooler Door | | • |
| Strip Curtain Replacement | | • |
| Door to Patio | | • |
| Standard lengths (inches) | 25"-30" | 25"-144" |
| Heat Options | | |
| Unheated | • | • |
| Electric | • | • |
| Steam/Hot Water | | • |

| Industrial Series | | | | | | | | | | |
|---|-----------------|-----------|-----------|-----------------------------------|-----------------------------------|--|--|--|--|--|
|  | Standard | HV | EP | WMI (Direct Drive) | WMH (Direct Drive) | Windguard 14 (Belt Drive) | Windguard 18 (Belt Drive) | Windguard 22 (Belt Drive) | Windguard 26 (Belt Drive) | Windguard 30 (Belt Drive) |
| Recommended Maximum Mounting Height (Feet) | | | | | | | | | | |
| Environmental Separation | 10' | 12' | 17' | 14' | 16' | 14' | 18' | 22' | 26' | 30' |
| Insect Control | 8' | 10' | 16' | | | | | | | |
| Commercial Entry | • | • | | | | | | | | |
| Freezer/Cooler Door | • | • | • | | | | | | | |
| Service Door | • | • | | | | | | | | |
| Shipping/Receiving | • | • | • | • | • | • | • | • | • | • |
| Automotive/Cargo | | • | • | • | • | • | • | • | • | • |
| Strip Curtain Replacement | • | • | • | • | • | • | • | • | • | • |
| Standard lengths (inches) | 36"-144" | 42"-144" | 48"-144" | 48"-216" | 48"-216" | 96"-192" | 96"-192" | 96"-192" | 96"-192" | 96"-192" |
| Heat Options | | | | | | | | | | |
| Unheated | • | • | • | • | • | • | • | • | • | • |
| Electric | • | • | • | • | • | • | • | • | • | • |
| Steam/Hot Water | • | • | • | • | • | • | • | • | • | • |
| Indirect Gas Fired | | • | • | • | • | • | • | • | • | • |
| Direct Gas Fired | | | | • | • | | | | | |